



eConnect™

Item no: see page 3



Type 2



eConnect™

Designed for extreme conditions

Premium charging cables made for performance, durability and unmatched user-friendliness in any conditions. eConnect cables can be used to charge all vehicles with a Type 2 interface.

Made for Nordic conditions:

eConnect cables remain soft and flexible, even in severe cold.

User-friendly:

eConnect cables are lightweight and have plugs with universal ergonomic design.

Durable:

Our robust cables and terminals are made for long term use.



Smart cap:

The retractable cap prevents it from collecting water and dirt during charging and from bumping into the car.

Environmentally friendly:



Our cables and plugs are recyclable

Accessories:

eConnect is available with a wide range of accessories.

Check defa.com for latest selection.

Specification

Ratings	See Item no. table
IP rating, connected/with end cap	IP44
Operating temperature [°C]	-40 to +55
Storage temperature [°C]	-50 to +85
Charging cable type	Mode 3
Connection to vehicle	Type 2 
Connection to charging station	Type 2 
Certification	IEC 62196-1, IEC 62196-2
Recycling	EE-waste

eConnect is available in the following versions:

Item no.	Current [A]*	Power [kW]*	Voltage [V~]*	Phase	Length [m]	Weight [kg]
711304	20	4,6	250	1	5,0	1,4
711305	20	4,6	250	1	7,5	1,8
711308	32	7,4	250	1	5,0	1,9
711309	32	7,4	250	1	7,5	2,4
711306	20	13,8	480	3	5,0	2,1
711307	20	13,8	480	3	7,5	2,7
711310	32	22,0	480	3	5,0	3,1
711311	32	22,0	480	3	7,5	4,0

***Maximum rating**

The actual charge rate is also determined by the onboard charger (car), the charging station and the temperature of the batteries.

DEFA is certified to the requirements of IATF 16949, ISO 9001, ISO 14001 and ISO 45001.

For more info, visit defa.com

